




Technische gegevens




Afb.1



Afb.2



Afb.3



Afb.4



DN ø	L [mm]	KG	F/F	EPDM	NBR	Uitrekking Afb.1 [mm]	Samendrukking Afb.2 [mm]	Laterale verplaatsing Afb.3 [mm]	Hoek afbuiging Afb.4 [a1 + a2]
1/2"	200	0,44	PN10	233012	236012	5	22	22	15°
3/4"	200	0,65	PN10	233034	236034	5	22	22	15°
1"	200	1,0	PN10	233100	236100	5	22	22	15°
1.1/4"	200	1,3	PN10	233112	236112	5	22	22	15°
1.1/2"	200	1,9	PN10	233114	236114	5	22	22	15°
2"	200	2,6	PN10	233200	236200	5	22	22	15°
2.1/2"	240	3,72	PN10	233212	236212	5	22	22	15°
3"	240	4,9	PN10	233300	236300	5	22	22	15°

Toepassing :

Water en distributievoorzieningen (voor EPDM) : T°C: -10°C + 95°C

Minerale oliën, koolwaterstoffen, brandstoffen (voor NBR) : T°C: -10°C + 70°C

Milder Bommel

Telefoon 026 - 325 91 03

Milder Rotterdam

Telefoon 010 - 415 99 83

info@milder.nl

www.milder.nl