

SEAMLESS BEND


$r \approx 1,5 \times d$

11°

long spigot for butt- and electrofusion-welding

NEW COMPLIANT WITH EN 12201 & EN 1555

PE 100



d1 [mm]	le1* [mm]	z1 [mm]	r [mm]	kg	
				[SDR 17]	[SDR 11]
50	100	150	75	0,10	0,20
63	100	160	95	0,20	0,30
75	100	170	113	0,30	0,50
90	150	210	135	0,60	0,80
110	150	220	165	0,90	1,30
125	150	235	188	1,20	1,80
140	150	250	210	1,60	2,40
160	150	260	240	2,20	3,30
180	150	280	270	3,10	4,50
200	150	310	300	4,20	6,20
225	150	350	338	6,00	8,80
250	250	430	375	9,00	13,40
280	250	450	420	11,90	17,50
315	300	500	496	16,70	24,70
355	300	590	560	25,10	37,00
400	300	650	637	34,90	51,70
450	300	700	711	47,70	70,60
500	350	750	783	63,20	93,30
560	350	800	877	84,30	124,70
630	350	850	955	113,60	167,90
710	350	1150	1128	194,90	288,60
800	350	1250	1274	268,80	397,90
900	400	1350	1430	367,30	544,10

other dimensions, materials and pressure classes on request
tolerance + / - 3°
*minimum "le1"

Advantages:

- **NEW:** compliant with EN 12201 & EN 1555
- suitable for gas, drinking water, sewage & mining applications