

SEAMLESS BEND


$r \approx 1,5 \times d$

90°

long spigot for butt- and electrofusion-welding

NEW COMPLIANT WITH EN 12201 & EN 1555

PE 100



d1 [mm]	le1 * [mm]	z1 [mm]	r [mm]	kg	
				[SDR 17]	[SDR 11]
50	100	200	75	0,20	0,20
63	100	220	95	0,30	0,40
75	100	260	113	0,50	0,70
90	150	300	135	0,70	1,10
110	150	380	165	1,40	2,10
125	150	400	188	1,90	2,80
140	150	440	210	2,60	3,90
160	150	480	240	3,70	5,50
180	150	530	270	5,20	7,60
200	150	560	300	6,70	9,90
225	150	590	338	8,80	13,10
250	250	730	375	13,60	20,20
280	250	750	420	17,40	25,70
315	300	900	496	26,50	39,20
355	300	1000	560	37,40	55,10
400	300	1050	637	49,10	72,70
450	300	1150	711	68,00	100,60
500	350	1300	783	95,30	140,90
560	350	1350	877	122,50	181,20
630	350	1600	955	186,40	275,60
710	350	1900	1128	281,10	416,20
800	350	2000	1274	371,40	549,80
900	400	2200	1430	515,20	763,20

other dimensions, materials and pressure classes on request
tolerance + / - 3°
*minimum "le1"

Advantages:

- **NEW:** compliant with EN 12201 & EN 1555
- suitable for gas, drinking water, sewage & mining applications